DO NOT use this machine unless you have received authorization from the Shop Coordinator



Hearing Protection must be worn at all times.

CALIFORNIA STATE UNIVERSITY

NORTHRIDGE



Safety glasses must be worn at all times.

Potential Hazards and Injuries

- ▲ Struck by
- A Burns
- ▲ Inhalation
- ▲ Noise

Pre-Operational Safety Checks

- Ensure tool is off when inspecting.
- Check for loose nuts, bolts and screws before each use.
- Make sure the air tube is securely attached.
- Inspect spark plug cap and lead to make sure they are not damaged, otherwise electric shock can occur.
- Clean air filter according to manufacturer's recommendations.
- Put on PPE
- Clean any spills with non-flammable absorbent and dispose of according to procedure.
- Inspect the area for people and wait until the area is clear.
- Check fuel lines and gas tank for leaks. If fuel is found do not start or operate.
- Ensure fuel mixture ratio per manufactures recommendation.



A dust mask must be worn at all times.



Gloves must be worn at all times.

Safe Practices During Operation

- ✓ Allow engine to warm up after starting.
- ✓ Use easy, short sweeping motion.
- Pause for pedestrians or motorists to move past immediate location.
- Follow noise ordinance restrictions when and where appropriate.

Ending Operations and Cleaning Up

✓ Allow engine to cool after use.

DON'T

- On not block blower pipe.
- 8 Do not touch muffler or exhaust.
- \otimes Do not touch the engine, it will be hot.
- 8 Avoid twisting and bending.
- O not point blower in the direction of other people.
- On not blow dust/debris towards bystanders or passersby.