

Our first script

```
> restart;  
Digits:=10;
```

Digits:= 10


(1)

```
> f:=x->x^3+4*x^2-10;
```

f:= x→x³ + 4x² - 10

(2)

```
> plot(f(x),x=-4..3);
```



The Algorithm

```
> a:=1.0;
```

a:= 1.0

(3)

```
> b:=2.0;
```

b:= 2.0

(4)

```
> FA:=f(a); f(b):=f(b); iter:=0;
```

*FA:= -5.000
f(2.0) := 14.000*

(5)

```
iter:= 0 (5)
```

```
> p:=a+(b-a)/2; FP:=f(p); FA*FP;  
p:= 1.500000000  
FP:= 2.37500000  
-11.87500000 (6)
```

since $FA*FP < 0$, the next interval becomes $[1,1.5]$

```
> b:=1.5; p:=a+(b-a)/2; FP:=f(p); iter:=1;  
  
b:= 1.5  
p:= 1.250000000  
FP:= -1.796875000  
iter:= 1 (7)
```

Now we check the sign of $FA*FP$

```
> FA*FP;  
8.984375000 (8)
```

and $a=p=1.25$ while $b=1.5$. Next, the new p and FA are

```
> a:=p; p:=a+(b-a)/2; FA:=f(p); iter:=2;  
a:= 1.250000000  
p:= 1.375000000  
FA:= 0.16210938  
iter:= 2 (9)
```

Next, since $FP*FA < 0$, b becomes $p=1.375$ and a is as before 1.25. The new p becomes

```
> b:=p; p:=a+(b-a)/2; iter:=3;  
b:= 1.375000000  
p:= 1.312500000  
iter:= 3 (10)
```

and so on.

Here is the full script:

```
> f:=x->x^3+4*x^2-10; a:=1.0; b:=2.0; FA:=f(a); FP:=f(a); iter:=0;  
f:= x→x3 + 4x2 - 10  
a:= 1.0  
b:= 2.0  
FA:= -5.000  
FP:= -5.000  
iter:= 0 (11)  
  
> while FP<>0 and (b-a)>=10(-4) do  
p:=a+(b-a)/2;  
FP:=f(p);  
iter:=iter+1;
```

```
if FA*FP>0 then a:=p;  
FA:=FP;  
else  
b:=p  
end if  
end do;
```

```
p:= 1.500000000  
FP:= 2.37500000  
iter:= 1  
p:= 1.250000000  
FP:= -1.796875000  
iter:= 2  
p:= 1.375000000  
FP:= 0.16210938  
iter:= 3  
p:= 1.312500000  
FP:= -0.848388672  
iter:= 4  
p:= 1.343750000  
FP:= -0.350982668  
iter:= 5  
p:= 1.359375000  
FP:= -0.096408842  
iter:= 6  
p:= 1.367187500  
FP:= 0.03235578  
iter:= 7  
p:= 1.363281250  
FP:= -0.032149969  
iter:= 8  
p:= 1.365234375  
FP:= 0.00007203  
iter:= 9  
p:= 1.364257812  
FP:= -0.016046697  
iter:= 10  
p:= 1.364746094  
FP:= -0.007989259  
iter:= 11  
p:= 1.364990234  
FP:= -0.003959107  
iter:= 12  
p:= 1.365112304  
FP:= -0.001943668  
iter:= 13  
p:= 1.365173340  
FP:= -0.000935846  
iter:= 14
```

Slightly more elegant script

```
> restart;  
> Digits:=10;
```

Digits:= 10

(13)

```
> f:=x->x^3+4*x^2-10; a:=1.0; b:=2.0; FA:=f(a); FP:=f(a);
```

f:= x → x³ + 4x² - 10

a:= 1.0

b:= 2.0

FA:= -5.000

FP:= -5.000

(14)

```
> for n from 1 to 20  
  while FP<>0 and (b-a)>=10^(-4) do  
    p[n]:=a+(b-a)/2;  
    FP:=f(p[n]);  
    if FA*FP>0 then a:=p[n];  
    FA:=FP;  
  else  
    b:=p[n]  
  end if  
end do;
```

p₁:= 1.500000000

FP:= 2.37500000

p₂:= 1.250000000

FP:= -1.796875000

p₃:= 1.375000000

FP:= 0.16210938

p₄:= 1.312500000

FP:= -0.848388672

p₅:= 1.343750000

FP:= -0.350982668

p₆:= 1.359375000

FP:= -0.096408842

p₇:= 1.367187500

FP:= 0.03235578

p₈:= 1.363281250

FP:= -0.032149969

p₉:= 1.365234375

FP:= 0.00007203

p₁₀:= 1.364257812

FP:= -0.016046697

p₁₁:= 1.364746094

```

FP:= -0.007989259
p12:= 1.364990234
FP:= -0.003959107
p13:= 1.365112304
FP:= -0.001943668
p14:= 1.365173340
FP:= -0.000935846

```

(15)

```

> solve({f(x)=0},{x});

```

$$\left\{ x = \frac{1}{3} (71 + 3\sqrt{105})^{1/3} + \frac{16}{3(71 + 3\sqrt{105})^{1/3}} - \frac{4}{3}, \left\{ x = -\frac{1}{6} (71 + 3\sqrt{105})^{1/3} - \frac{4}{3} + \frac{1}{2} I\sqrt{3} \left(\frac{1}{3} (71 + 3\sqrt{105})^{1/3} - \frac{16}{3(71 + 3\sqrt{105})^{1/3}} \right) \right\}, \left\{ x = -\frac{1}{6} (71 + 3\sqrt{105})^{1/3} - \frac{4}{3} - \frac{1}{2} I\sqrt{3} \left(\frac{1}{3} (71 + 3\sqrt{105})^{1/3} - \frac{16}{3(71 + 3\sqrt{105})^{1/3}} \right) \right\} \right\}$$

(16)

```

> evalf(%);
{x = 1.365230013}, {x = -2.682615007 + 0.3582593602 I}, {x = -2.682615007 - 0.3582593602 I}

```

(17)

And here is another stopping criterion:

```

> restart; f:=x->x^3+4*x^2-10; a:=1.0; b:=2.0; FA:=f(a); FP:=f(a);
iter:=0;

```

$$f := x \rightarrow x^3 + 4x^2 - 10$$

$$a := 1.0$$

$$b := 2.0$$

$$FA := -5.000$$

$$FP := -5.000$$

$$iter := 0$$

(18)

```

> while FP<>0 and abs(FP)>=10^(-4) do
p:=a+(b-a)/2;
FP:=f(p);
iter:=iter+1;
if FA*FP>0 then a:=p;
FA:=FP;
else
b:=p;
end if
end do;

```

$$p := 1.500000000$$

$$FP := 2.375000000$$

```

        iter:= 1
        p:= 1.250000000
        FP:= -1.796875000
        iter:= 2
        p:= 1.375000000
        FP:= 0.16210938
        iter:= 3
        p:= 1.312500000
        FP:= -0.848388672
        iter:= 4
        p:= 1.343750000
        FP:= -0.350982668
        iter:= 5
        p:= 1.359375000
        FP:= -0.096408842
        iter:= 6
        p:= 1.367187500
        FP:= 0.03235578
        iter:= 7
        p:= 1.363281250
        FP:= -0.032149969
        iter:= 8
        p:= 1.365234375
        FP:= 0.00007203
        iter:= 9

```

(19)

And still another stopping criterion:

```

> restart; f:=x->x^3+4*x^2-10; a:=1.0; b:=2.0; FA:=f(a); FP:=f(a);
  iter:=0;

```

```

        f:= x→x3 + 4x2 - 10
        a:= 1.0
        b:= 2.0
        FA:= -5.000
        FP:= -5.000
        iter:= 0

```

(20)

```

> while FP<>0 and (b-a)/b>=10(-4) do
  p:=a+(b-a)/2;
  FP:=f(p);
  iter:=iter+1;
  if FA*FP>0 then a:=p;
  FA:=FP;
  else
  b:=p
  end if
end do;

```

```

        p:= 1.500000000
        FP:= 2.375000000
        iter:= 1
        p:= 1.250000000

```

FP:= -1.796875000
iter:= 2
p:= 1.375000000
FP:= 0.16210938
iter:= 3
p:= 1.312500000
FP:= -0.848388672
iter:= 4
p:= 1.343750000
FP:= -0.350982668
iter:= 5
p:= 1.359375000
FP:= -0.096408842
iter:= 6
p:= 1.367187500
FP:= 0.03235578
iter:= 7
p:= 1.363281250
FP:= -0.032149969
iter:= 8
p:= 1.365234375
FP:= 0.00007203
iter:= 9
p:= 1.364257812
FP:= -0.016046697
iter:= 10
p:= 1.364746094
FP:= -0.007989259
iter:= 11
p:= 1.364990234
FP:= -0.003959107
iter:= 12
p:= 1.365112304
FP:= -0.001943668
iter:= 13